What is claimed is:

50°/

5

5

5

1. A method for reducing colormap flashing on a display system, the display system having a frame buffer which provides a single hardware colormap, the method comprising the steps of:

intercepting a request from an application program for an allocation of a private colormap; and

transparently simulating the allocation of the private colormap using a default colormap.

2. The method of claim 1, wherein said step of transparently simulating the allocation of a private colormap further comprises:

allocating a secondary lookup table for storing information received from said application program relating to one or more requested colors privately allocated by said application program;

performing a closest match of said requested color to a color stored in said default colormap; and

returning said closest match to said application program.

3/ A computer program product, comprising:

a computer usable code storage medium;

computer readable code embodied in said storage medium for reducing colormap flashing on a display system, the display system having a single hardware colormap, the computer readable code comprising:

computer readable dode devices to cause a computer to effect intercepting a request from an application program for an allocation of a private colormap; and

computer readable code devices to cause a computer to effect transparently simulating the allocation of the private colormap using a default colormap.

- 4. The computer program product of claim 3, wherein said computer readable program code devices configured to cause a computer to effect transparently simulating the allocation of a private colormap further comprises:
- computer readable code devices to cause a computer to effect allocating a secondary lookup table for storing information received from said application program relating to one or more requested colors privately allocated by said application program;

computer readable code devices to cause a computer to effect

10 performing a closest match of said requested color to a color stored in said default colormap; and

computer readable code devices to cause a computer to effect returning said closest match to said application program.

ADD AND ADD

5